



Lower Wattage, Higher Efficiency Offering

100-347V & 100-277V Models

Unique, Long-Lasting Design

3500K, 4000K & 5000K

FPH2-Series LED Hybrid Flat Panels



Intertek

The FPH2-Series Hybrid LED Flat Panel ceiling light is a high performance LED panel that uses a unique back-lit design to provide a longer lasting lighting solution.

With a flicker-free, fully dimmable design that requires no warm-up, they produce very little heat and are the perfect replacement for traditional fluorescent lighting or low-end edge-lit flat panels found in offices, hospitals, schools and more.

Key Features & Benefits

- Back-lit design requires no light guide plate
- Lightweight design for quicker installs
- High-strength design resists bowing when hung
- Large junction box for quick and easy daisy chain connections
- 100-347V models make it easy to meet any job requirement
- Post-painted white frame
- Designed to fit directly into existing suspended T-bar ceilings
- Low profile: will fit into any plenum space
- Versatile installation options including hanging via aircraft cable or surface mounting (optional accessories)

WHY CHOOSE THIS FIXTURE?

SLIM PROFILE

Fits into any plenum space

LARGER JUNCTION BOX

A large 6" x 4" junction box leaves more room for connections and makes it easy to install

NO LIGHT GUIDE PLATE

Eliminates the potential of yellowing

WHITE POST-PAINTED FRAMES

Matches with any decor right out of the box

MULTIPLE MOUNTING OPTIONS

Ready to install into existing T-bars out of the box; or add accessories for additional mounting flexibility



Aircraft Cable Kit



Surface Mount Kit

100-277V Models (DLC Standard)

MODEL#	WATTAGE	VOLTAGE	LUMENS	EFFICACY	CCT	SIZE
FPH2-1430S40-1	30W	100-277V	3,559 lm	117 lm/W	4000K	1 x 4
FPH2-2230S40-1	30W	100-277V	3,330 lm	109 lm/W	4000K	2 x 2
FPH2-2240S40-1	40W	100-277V	4,537 lm	114 lm/W	4000K	2 x 2
FPH2-2430S35-1	30W	100-277V	3,226 lm	112 lm/W	3500K	2 x 4
FPH2-2430S40-1	30W	100-277V	3,294 lm	115 lm/W	4000K	2 x 4
FPH2-2430S50-1	30W	100-277V	3,429 lm	117 lm/W	5000K	2 x 4
FPH2-2440S35-1	40W	100-277V	4,682 lm	125 lm/W	3500K	2 x 4
FPH2-2440S40-1	40W	100-277V	4,725 lm	126 lm/W	4000K	2 x 4
FPH2-2440S50-1	40W	100-277V	4,811 lm	128 lm/W	5000K	2 x 4

100-347V Models (DLC Standard)

MODEL#	WATTAGE	VOLTAGE	LUMENS	EFFICACY	CCT	SIZE
FPH2-2230S40-3	30W	100-347V	3,318 lm	117 lm/W	4000K	2 x 2
FPH2-2240S40-3	40W	100-347V	4,706 lm	115 lm/W	4000K	2 x 2
FPH2-2430S35-3	30W	100-347V	3,061 lm	109 lm/W	3500K	2 x 4
FPH2-2430S40-3	30W	100-347V	3,169 lm	112 lm/W	4000K	2 x 4
FPH2-2430S50-3	30W	100-347V	3,282 lm	116 lm/W	5000K	2 x 4
FPH2-2440S35-3	40W	100-347V	4,120 lm	110 lm/W	3500K	2 x 4
FPH2-2440S40-3	40W	100-347V	4,186 lm	111 lm/W	4000K	2 x 4
FPH2-2440S50-3	40W	100-347V	4,261 lm	114 lm/W	5000K	2 x 4

100-347V Models (DLC Premium)

MODEL#	WATTAGE	VOLTAGE	LUMENS	EFFICACY	CCT	SIZE
FPH2-1430P40-3	30W	100-347V	3,728 lm	128 lm/W	4000K	1 x 4
FPH2-2220P40-3	20W	100-347V	2,646 lm	136 lm/W	4000K	2 x 2
FPH2-2230P40-3	30W	100-347V	3,705 lm	128 lm/W	4000K	2 x 2
FPH2-2430P40-3	30W	100-347V	3,776 lm	133 lm/W	4000K	2 x 4
FPH2-2440P40-3	40W	100-347V	4,912 lm	129 lm/W	4000K	2 x 4

Optional Accessories

FPH-ACK11	Aircraft Cable for 1x4 and 2x2 Flat Panels	FPH-14SMK1	Surface Mount Kit for 1x4 Flat Panels
FPH-ACK21	Aircraft Cable for 2x4 Flat Panels	FPH-22SMK1	Surface Mount Kit for 2x2 Flat Panels
		FPH-24SMK1	Surface Mount Kit for 2x4 Flat Panels